



- Aluminium 2 or 3 sections combination ladder.
- 24x24 mm square non-slip rungs.
- Steel hinges.
- Stairwell ladder.
- Colours:

Plastics



Safety devices



The steel hinges hook to each rung to obtain a stairwell ladder, if necessary.



Code	(mm)	Rungs number	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(kg)	(m <sup>3</sup> )	
<b>2 SECTIONS</b>													
SL180-2	25x60	2x6	174	286	166	113	376	256	76	10	7,0	0,09	8028406107781
SL200-2	25x60	2x7	202	314	193	131	404	283	76	10	8,5	0,10	8028406107750
SL230-2	25x60	2x8	230	370	220	149	460	310	76	10	10,0	0,11	8028406107835
SL260-2	25x65	2x9	258	426	247	169	516	337	86	11	11,0	0,14	8028406107767
SL290-2	25x65	2x10	286	454	274	186	544	364	86	11	12,5	0,15	8028406107798
SL310-2	25x65	2x11	314	510	301	204	600	391	96	11	14,0	0,16	8028406107774
<b>3 SECTIONS</b>													
SL180-3	25x60	3x6	174	398	166	113	488	363	76	15	10,0	0,13	80284061067804
SL200-3	25x60	3x7	202	426	193	131	516	404	76	15	12,0	0,15	8028406106715
SL230-3	25x60	3x8	230	510	220	149	600	445	76	15	13,4	0,17	8028406107705
SL260-3	25x60/80	3x9	258	594	247	169	684	486	86	17	15,2	0,21	8028406106722
SL290-3	25x65/80	3x10	286	622	274	186	712	527	86	18	18,0	0,25	8028406107811
SL310-3	25x80	3x11	314	706	301	204	796	568	96	18	19,2	0,27	8028406106739
SL350-3	25x80	3x12	342	818	328	225	908	609	96	20	21,4	0,33	8028406107828



Lower section: **47,8 cm**  
 Middle section: **41,4 cm**  
 Upper section: **34,5 cm**



EN131  
EUROPEAN NORM



**PLUS**

Stairwell ladder



Anti unthreading stops  
(EN 131)