

BRIKO *plus*

- Aluminium telescopic ladder provided with steel and aluminium die casting hinges.
- It fits itself to all uses.
- Rung/stile connection through six points of robotized welding.



A-FRAME STEP
POSITION:

The automatic hinge allows the free movement with opening stop.



		Code	rungs number	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(kg)	(m³)	Ean
150 kg	EN131 European Norm 	BKPL/1	4x3	98	310	152	86	400	265	51	9,40	0,093	8028406103035
		BKPL/1,5	2x3+2x4	129	390	180	110	480	295	51	10,20	0,123	8028406103042
		BKPL/2	4x4	129	430	208	128	520	325	62	12,00	0,135	8028406103059
100 kg	D.LGS 81/2008 	BKPL/3	2x4+2x5	158	490	235	143	580	355	62	12,60	0,164	8028406103066
		BKPL/4	4x5	158	550	265	168	640	385	62	13,80	0,164	8028406103073
		BKPL/5	4x6	188	610	292	210	700	415	71	16,40	0,210	8028406103080



This product is delivered with a PVC wrap film and product leaflet



150 kg
MAX



EN131
EUROPEAN NORM



BKPL/1-1,5-2
2006/4493

100 kg
MAX



BKPL/3-4
2006/4494
BKPL/5
2006/4495



30x30 mm square
non-slip rungs



Steel automatic hinge

Rung locking pin,
made from
aluminium die casting
and stainless steel

