

# CASTIGLIA

- Very firm aluminium warehouse step with castors and double handrails.
- Folding for transport and storage.
- Climbing side with 60° slope for a more comfortable ascent.



Strong aluminium die casting connection




Large and non-slippery sheet aluminium platform (48x77 cm). It's fitted with big tool tray




Code	treads number	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(kg)	(m <sup>3</sup> )	Ean
CA0/50	2 + plat.	68,0	175,0	250	68,0	110,0	199,0	23	0,20	8028406000006
CA0/75	3 + plat.	87,0	193,0	270	74,0	128,0	224,0	26	0,31	8028406000174
CA1/100	4 + plat.	108,0	214,5	290	76,0	144,5	249,0	30	0,40	8028406000013
CA2/125	5 + plat.	133,0	238,0	310	82,0	160,5	274,0	33	0,54	8028406000020
CA3/150	6 + plat.	154,0	262,0	330	86,0	174,0	299,0	36	0,60	8028406000037
CA4/175	7 + plat.	174,5	282,0	350	89,5	187,0	324,0	38	0,64	8028406000044
CA5/200	8 + plat.	195,0	304,0	380	95,0	198,5	340,0	40	0,69	8028406000051
CA6/225	9 + plat.	219,0	327,0	400	98,5	214,5	373,0	43	0,79	8028406000068
CA7/250	10 + plat.	239,5	347,5	420	104,0	227,5	399,0	46	0,90	8028406000075
CA8/275	11 + plat.	261,0	369,0	440	107,5	241,0	424,0	49	0,96	8028406000082
CA10/300	13 + plat.	305,0	413,0	480	116,0	265,0	474,0	56	1,04	8028406000099
CA11/325	14 + plat.	328,5	437,0	505	122,0	275,0	499,0	59	1,14	8028406000105
CA12/350	15 + plat.	347,5	453,5	525	124,5	293,0	526,0	62	1,24	8028406000112
CA13/375	16 + plat.	371,0	479,0	550	132,0	313,5	547,0	66	1,34	8028406000129
CA14/400	17 + plat.	392,0	499,7	570	134,0	318,0	575,0	70	1,48	8028406000136
CA15/425	18 + plat.	415,0	524,0	595	138,0	331,5	599,0	73	1,54	8028406000143
CA16/450	19 + plat.	435,0	542,0	615	139,0	344,5	626,0	77	1,66	8028406000150
CA18/500	21 + plat.	486,0	595,0	660	151,0	382,0	675,0	84	1,89	8028406000167
D660/1	2 small stabilisers (till CA7/250)									8028406103011
D662/1	2 big stabilisers (from CA8/275 to CA14/400)									8028406103028



Format for transport





Stabilisers  
EU EN131  
EUROPEAN NORM

150 kg  
MAX

EU EN131  
EUROPEAN NORM

With 2 stabilisers and  
TUV-GS certificate



S 60080258

100 kg  
MAX


Without stabilisers



The right-angle  
back side  
allows a better  
approach to  
the working point



150 mm



150 mm treads width.  
Stile/tread connection through  
10 points without welding



Folding handles



80 mm Ø turning and self-  
blocking front castors



125 mm Ø rear castors  
with brake