

“PRIMA”

- 2 or 3 sections aluminium rope-operated extension ladder.
- It's fitted with a steel locking fall hook.
- Telescopic stabiliser bar in standard production.


EN131
EUROPEAN NORM

2001/1677 2001/1676
2001/1674 2001/1678
2001/1672 2001/1675
2001/1673

30x30 rhomboidal non-slip rungs with
68° slope

Steel sliding devices coated
with nylon


Steel parts coated with nylon



Steel locking fall hook mechanism

1 Main rope

2 Secondary rope to recall the locking fall hook

Code	(mm)	rungs number	(cm)	(cm)	(cm)	(cm)	(kg)	(m ³)	Ean	
2 SECTION										
P320-2F	25x80	9 + 10	324	510	600	14	20,5	0,23	8028406001003	
P350-2F	25x80	10 + 11	354	570	660	14	22,5	0,25	8028406000990	
P420-2F	25x90	12 + 13	424	690	780	16	26,5	0,33	8028406000983	
P450-2F	25x90	13 + 14	454	750	840	16	28,5	0,36	8028406000976	
3 SECTION										
P320-3F	25x80	9+10+10	324	720	810	17	30,5	0,30	8028406000969	
P350-3F	25x80	10+11+11	354	810	900	17	32,5	0,33	8028406000952	
P420-3F	25x90	12+13+13	424	990	1080	22	37,5	0,46	8028406000945	
P450-3F	25x90	13+14+14	454	1080	1170	22	40,5	0,50	8028406000938	

This product is delivered with a PVC wrap film and product leaflet


Stabiliser bar
83/128 cm

Lower section: 50 cm
Middle section: 45 cm
Upper section: 39 cm