

# "PRIMA"

- Aluminium treading ladder.
- Articulated rubber feet in standard production.
- Especially recommended for interior works and as shelf-ladder.



Plug-in top feet.


**EN131**  
EUROPEAN NORM

2012/3102  
2012/3103


S 60080283


ACCESSORY:  
Steel hooks

45  
cm

Stile/treads  
connection through  
double  
expansion  
mechanism


85 mm non-slip treads


Articulated feet. Steel  
structure coated with  
anti-slip rubber as  
standard

| Code     | (mm)       | treads<br>number | (cm) | (cm) | (cm) | (kg) | (m <sup>3</sup> ) | Ean           |
|----------|------------|------------------|------|------|------|------|-------------------|---------------|
| PM 205/L | 25x65      | 6                | 205  | 190  | 295  | 4,3  | 0,07              | 8028406001928 |
| PM 265/L | 25x65      | 8                | 265  | 245  | 355  | 5,5  | 0,09              | 8028406001935 |
| PM 295/L | 25x65      | 9                | 295  | 275  | 385  | 7,0  | 0,10              | 8028406001942 |
| PM 355/L | 25x65      | 11               | 355  | 330  | 445  | 7,7  | 0,11              | 8028406001959 |
| PM 411/L | 25x65      | 13               | 415  | 385  | 500  | 8,8  | 0,13              | 8028406001966 |
| PM 445/L | 25x65      | 14               | 445  | 415  | 535  | 9,4  | 0,14              | 8028406001973 |
| PM 505/L | 25x65      | 16               | 505  | 470  | 595  | 11,8 | 0,16              | 8028406001980 |
| PM 561/L | 25x65      | 18               | 561  | 525  | 650  | 12,6 | 0,18              | 8028406001997 |
| PM 595/L | 25x80      | 19               | 595  | 555  | 685  | 13,5 | 0,19              | 8028406002000 |
| PM 655/L | 25x80      | 21               | 655  | 610  | 745  | 14,6 | 0,20              | 8028406002017 |
| FE-119/A | Steel hook |                  |      |      |      |      |                   | 8028406106579 |

This product is delivered with a PVC wrap film and product leaflet