

DAMA

- Aluminium 2 or 3 sections combination ladder.



IT DOESN'T BEND!!

The big stiles dimensions avoid the ladder bending when it's completely extended.



Code	(mm)	rungs number	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(kg)	(m ³)	Ean
------	------	--------------	------	------	------	------	------	------	------	------	------	-------------------	-----

2 SECTIONS

D200-2	25x65	2x6	202	292	193	126	382	313	77	11	10,0	0,11	8028406001010
D260-2	25x65	2x8	262	412	250	162	502	370	93	11	12,5	0,14	8028406001027
D290-2	25x90	2x9	292	472	279	194	562	399	93	15	17,4	0,22	8028406001034
D350-2	25x90	2x11	354	594	338	229	684	458	114	15	21,2	0,27	8028406001041
D380-2	25x90	2x12	384	654	364	257	744	486	114	15	24,0	0,29	8028406001058

3 SECTIONS

D200-3	25x65	3x6	202	382	195	130	472	385	77	16	15,0	0,16	8028406001065
D260-3	25x65	3x8	262	562	252	166	652	442	93	16	18,8	0,21	8028406001072
D290-3	25x90	3x9	292	652	280	197	742	471	93	21	26,8	0,31	8028406001089
D350-3	25x90	3x11	354	834	340	235	924	530	114	21	30,8	0,37	8028406001096
D380-3	25x90	3x12	384	921	369	264	1011	560	114	21	32,5	0,40	8028406001102



Lower section: **50 cm**
 Middle section: **45 cm**
 Upper section: **39 cm**

This product is delivered with a PVC wrap film and product leaflet



The aluminium die casting hinges allow an easy stiles sliding. Simple to open in A-frame position. Upper section fitted with 100 mm wall wheels



Alum anti-splay bars connected to stiles through expansion in the rungs' holes. Strong restraint straps on a few models
Excluding:

- D200-2** with anti-splay restraint straps
- D260-2** with anti-splay restraint straps
- D290-2** with anti-splay restraint straps



Ribbed aluminium stabiliser bar



EN131
EUROPEAN NORM



UPDATE NEW NORM EN131: 01/18



30x30 rhomboidal non-slip rungs with 68° slope



Steel safety hooks fixed to the stiles with stay bolts



Anti unthreading stops (EN 131)