

“PRIMA”

- 2 or 3 sections aluminium rope-operated extension ladder.
- It's fitted with a steel locking fall hook.
- Telescopic stabiliser bar in standard production.

150 kg MAX
EU EN131 EUROPEAN NORM
POLITECNICO MILANO
UPDATE NEW NORM EN131: 01/18




30x30 rhomboidal non-slip rungs with 68° slope



Steel sliding devices coated with nylon



Steel locking fall hook mechanism
1 Main rope
2 Secondary rope to recall the locking fall hook



Steel parts coated with nylon

Code	(mm)	rungs number	(cm)	(cm)	(cm)	(cm)	(kg)	(m ³)	Ean
2 SECTION									
P320-2F	25x80	9 + 10	324	510	600	14	20,5	0,38	8028406001003
P350-2F	25x80	10 + 11	354	570	660	14	22,5	0,56	8028406000990
P420-2F	25x90	12 + 13	424	690	780	16	26,5	0,46	8028406000983
P450-2F	25x90	13 + 14	454	750	840	16	28,5	0,77	8028406000976
3 SECTION									
P320-3F	25x80	9+10+10	324	720	810	17	30,5	0,41	8028406000969
P350-3F	25x80	10+11+11	354	810	900	17	32,5	0,60	8028406000952
P420-3F	25x90	12+13+13	424	990	1080	22	37,5	0,50	8028406000945
P450-3F	25x90	13+14+14	454	1080	1170	22	40,5	0,83	8028406000938

This product is delivered with a PVC wrap film and product leaflet



Stabiliser bar
83/128 cm



Lower section: 50 cm
Middle section: 45 cm
Upper section: 39 cm