

BRIKO plus

- Aluminium telescopic ladder provided with steel and aluminium die casting hinges.
- It fits itself to all uses.
- Rung/stile connection through six points of robotized welding.



A-FRAME STEP POSITION:
The automatic hinge allows the free movement with opening stop.



	Code	Rungs number.	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(kg)	(m ³)	Codice Ean
150 kg EN131 European Norm	BKPL/1	4x3	92	288	143	93	380	260	52	9,50	0,12	8028406103035
	BKPL/1,5	2x3+2x4	120	344	170	108	435	285	52	10,50	0,15	8028406103042
	BKPL/2	4x4	120	400	198	122	490	315	62	12,50	0,18	8028406103059
100 kg D.LGS 81/2008	BKPL/3	2x4+2x5	148	456	225	137	550	340	62	13,00	0,22	8028406103066
	BKPL/4	4x5	148	512	252	152	605	370	62	14,00	0,22	8028406103073
	BKPL/5	4x6	176	570	280	167	660	390	72	16,50	0,31	8028406103080

This product is delivered with a PVC wrap film and product leaflet





SUPER PRO 600 RANGE




EN131
EUROPEAN NORM



BKPL/1-1,5-2
2006 / 4493



BKPL/3-4
2006 / 4494
BKPL/5
2006 / 4495



30x30 mm square non-slip rungs



PROFESSIONAL
INTENSIVE USE



240 mm

Steel automatic hinge



Rung locking pin, made from aluminium die casting and stainless steel
DESIGN FACAL

