

Casta

- Aluminium warehouse step.
- Folding, with castors and telescopic stabilisers.
- Use with opened stabilisers.



Folding guardrails

Fast opening and closing thanks to
RAPID SYSTEM



Code	Treads number	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(cm)	(kg)	(m ³)	Ean
EN131											
CTA-3	2 + plat.	75	176	255	102	81	81	194	22	0,30	8028406106111
CTA-4	3 + plat.	103	204	283	121	173	81	224	27	0,34	8028406106128
CTA-5	4 + plat.	131	232	311	140	188	81	254	28	0,39	8028406106135
CTA-6	5 + plat.	159	260	339	159	216	81	284	29	0,43	8028406106142
CTA-7	6 + plat.	187	288	376	178	250	106	314	30	0,48	8028406106159
CTA-8	7 + plat.	215	316	395	197	268	106	344	32	0,53	8028406106166
CTA-9	8 + plat.	243	344	423	216	274	127	374	34	0,57	8028406106173
CTA-10	9 + plat.	271	372	451	235	337	127	404	36	0,62	8028406106180
CTA-11	10 + plat.	299	400	479	254	343	139	434	38	0,66	8028406106197



24x60 mm



Width - with closed stabilisers
68 cm



External stiles width
51 cm



Slope **68°**

This product is delivered with a PVC wrap film and product leaflet



UPDATE NEW NORM EN131: 01/18



ADVANCED TECHNOLOGY!
Large folding platforms with holes to keep it clean



85 mm non-slip aluminium treads



Stile/tread connection through triple expansion and crimping



80 mm Ø turning and self-blocking front castors

Stabiliser bar with aluminium die casting supports for castors



It means: aromatic polycyclic hydrocarbons plastic parts are heavy metal-free (Zinc, Chrome, and Cadmium)

