

“PRIMA”

- Aluminium rung leaning ladder.
- Possibility to set up articulated feet, thanks to a pre-drilling under the rubber shoes.



plug-in top feet

150
kg
MAX

EN131
EUROPEAN NORM


UPDATE NEW NORM EN131: 01/18

ACCESSORIES



55x120 mm

Small articulated feet. Steel structure coated with rubber – 25x65 mm stile size

for codes PM 205/S - PM 265/S
- PM 295/S



Alum die casting connector with small articulated foot for stabilizing bar
Code: PSP/B



Steel hooks
Code: FE-119/A


Stabilising bar from the code PM 355/SB

45
cm

Thanks to the rung slope at 68°, feet and legs don't get tired (FACAL Patent)



Sloped rhomboidal non-slip rungs.



5 cm high anti-slip shoes, for codes:
PM 205/S - PM 265/S
PM 295/S



WITHOUT STABILISING BAR

Code	(mm)	N. gr.	(cm)	(cm)	(cm)	(cm)	(kg)	(m³)	Ean
PM 205/S	25x65	6	199	190	295	-	3,90	0,06	8028406001645
PM 265/S	25x65	8	259	245	355	-	5,00	0,07	8028406001652
PM 295/S	25x65	9	290	275	385	-	6,30	0,08	8028406001669

WITH STABILISING BAR FROM PRODUCTION 2018

PM 355/SB	25x65	11	352	330	445	89	8,10	0,10	8028406111405
PM 411/SB	25x65	13	409	385	500	89	9,10	0,12	8028406111412
PM 445/SB	25x65	14	440	415	535	107	9,90	0,13	8028406111429
PM 505/SB	25x65	16	507	470	595	107	10,30	0,15	8028406111436
PM 561/SB	25x65	18	562	525	650	107	10,80	0,16	8028406111443
PM 595/SB	25x80	19	597	555	685	107	13,80	0,21	8028406111450
PM 655/SB	25x80	21	656	610	745	120	15,00	0,24	8028406111467

PSP	Small articulated foot 55x120 mm – 25x65 mm stile size								8028406106647
PSG	Big articulated foot 60x180 mm – 25x80 mm stile size								8028406106654
PSP/B	Alum die casting connector with small articulated foot for stabilizing bar								8028406112303
FE-119/A	Steel hook.								8028406106579

This product is delivered with a PVC wrap film and product leaflet

